



Rack Mount Power Supplies

RM Series

Features

- Over voltage, Over current & Short circuit protected
- Modular 2U standard 19" rack mount chassis
- Stable DC output ensures clearer video images
- Power cord (PC) for use with typical wall plug in lieu of hard-wired 240 VAC

Applications

- CCTV
- Access Controls
- Electromagnetic locks

Description

The RM Series provides clean, filtered and regulated DC/AV voltage. Suitable for all electronic devices, including access controls, electromagnetic locks and CCTV. This series is designed with up to 16 individual fused outputs for powering all electronic devices, enabling easy installation and long term reliability.



Specification/Part No	RMAC2410-1600A-2U	RMAC2405-0800A-2U	RMDC1220-1600A-1U	RMDC1210-0800A-1U
Input Voltage	190-240V AC	190-240V AC	190-240V AC	190-240V AC
Input Frequency	50-60Hz	50-60Hz	50-60Hz	50-60Hz
Output voltage	24-28V AC	24-28V AC	12V DC	12V DC
Output Current	10Amp	5Amp	20Amp	10Amp
Efficiency	≥70%	≥85%	≥85%	≥85%
Overcurrent Protection			24A4±5%	12A±5%
Output Channel	16 channel	8 channel	16 channel	8 channel
Dimensions	483x250x88mm	483x250x88mm	483x250x44mm	483x250x44mm
Weight	7.9kg	5.8kg	3.9kg	3.4kg