

SPS-035-D Series

35W Dual Output



99 x 82 x 35 mm



Features:

- * Power ON with LED indicator
- * Built-in EMI filter, low ripple noise
- * Over load, over voltage, short circuit protection
- * 100% 50 burn-in test
- * UL, cUL, CB, CE Certified


Specification:

INPUT	Voltage	universal full range 85~264 VAC or 120~375VDC							
	Frequency	47 ----- 63 Hz							
	Current	<1.0A @100V AC, full load condition							
	Inrush Current	<30A@115V / <50A@230V AC input, full load condition. Cold start at 25 ambient							
	Leakage Current	<1.0mA@240V AC input							
OUTPUT	Model NO.	SPS-035-D1		SPS-035-D2		SPS-035-D3		SPS-035-D4	
	Output	V1	V2	V1	V2	V1	V2	V1	V2
	Voltage	+5V	+12V	+5V	+24V	+12V	-12V	+15V	-15V
	Min. Load	0.3A	0.1A	0.3A	0.1A	0.3A	0.1A	0.3A	0.1A
	Max. Load	4.0A	1.5A	4.0A	1.3A	1.5A	1.5A	1.3A	1.3A
	Regulation	±3%	±5%	±3%	±5%	±2%	±5%	±2%	±5%
	Ripple Noise (MAX.)	50mV	120mV	50mV	240mV	120mV	120mV	150mV	200mV
	Efficiency (MIN.)	75%		75%		76%		76%	
	MAX Power	35W							
PROTECTION	Over Voltage	5.8~7.0V	--	5.8~7.0V	--	13.8~17.5V	--	17.3~21.0V	--
	Over Load	Over 105% ~ 180% of rating, recovers automatically after fault condition has been removed.							
	Short Circuit	Shutdown, recovers automatically after fault condition has been removed.							
OTHERS	Rise time	<20mS							
	Hold up time	>40mS@230V							
	Setup time	<2.0Sec @115V, <0.8Sec @230V							
	Cooling	Natural Cooling							
Environment	Temperature	Operating: -10~70 ; De-rating: 45 ~70 : 2.5%/ . Storage: -10~+75							
	Humidity	Operating: 20% ~ 85%; Storage: 10% ~ 95% (non condensing)							
M.T.B.F.		472K hours							
SAFETY		UL 60950-1 st , CSA C22.2 No.60950-1-03 1 st approved. TUV EN 60950-1 st , IEC 60950-1 st , EMKO-TSE (74-SEC)207/94 standard.							
EMC	EMI	EN 55022 CLASS B : EN 61000-3-2,3、FCC CFR 47 PART 15 CLASS B、CNS 13438 CLASS B.							
	EMS	EN 55024 : EN 61000-4-2,3,4,5,6,8,11.							

Specifications subject to change without notice.

Dimension:

SPS-035-D Series



NOTES:

1. MATERIAL : COVER & CHASSIS SPCC, NICKLE PLATED.
2. TERMINAL BLOCK : 6P, PITCH 8.25 mm.(STANDARD)
3. UNIT:mm.